



**PP Acrylic 28my LN H.T.
AC 820LN**
TECHNICAL DATA SHEET



DESCRIPTION:

High-grade water based low noise acrylic tape.
Carrier BOPP 28my film, with 22my adhesive for manual carton sealing packaging applications.
Low noise properties. Available also in red, yellow, blue and green.

APPLICATIONS:

- Manual carton sealing.
- Adhesion on uneven surfaces due to high amount of adhesive.
- Particularly suitable for all sorts of packaging applications.
- Suitable for cold and hot temperatures.

PROPERTIES:

- Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- Resistance to temperature changes.
- Longevity of application

NOMINAL VALUES:

Backing
Biaxially Oriented Polypropylene (BOPP)

Adhesive
Acrylic (Water-based)

Tensile Strength MD
140 ± 30 (N/mm²)
TM 5004 by Afera

Elongation at Break MD
140 ± 30 (%)
TM 5004 by Afera

Peel Adhesion on Stainless Steel
5.8 ± 1 (N/25mm)
TM 5001 by Afera

Shear to Steel
Over 170 (h, 25mm x 25mm on stainless steel, 23°C)
TM 5012 by Afera

Rolling Ball Tack
Under 3 (cm)
PSTC-6 (PSTC)

Film thickness
28 ± 1(mic)

Film Colors Transparent

Adhesive Color Transparent Brown White

Red Yellow Blue Green

Effective: June 2017



SVP Négoce, ZAC du Clos Neuf, 16 rue Denis Papin, 14840 DEMOUVILLE
Tél : 02 31 26 16 64
E-mail : contact@svpnegoce.com
RCS de Caen : 822 624 805 TVA intracommunautaire : FR 39 822 624 805
N° de SIRET : 822 624 805 00039 Code APE : 4690Z